

# SAFETY DATA SHEET

## A.W.F. FLOORTECT H.B. BASE

### 1. PRODUCT AND COMPANY IDENTIFICATION

Product Name	A.W.F. FloorTect H.B. Base
Supplier	A.W.F. SMS Ltd
Address	Unit I D Brymau 3 Estate River Lane Saltney Chester, CH4 8RQ
Phone Number	01244 - 677833
Fax Number	01244 - 677844

### 2. COMPOSITION/INFORMATION ON INGREDIENTS

Substance/preparation

BISPHENOL A - EPOXY RESIN (Mn <=700)

CAS number	% by weight	EC number	Classification
025068-38-6	30 - 40%	500-033-5	Xi; R36/38, R43, N; R51/53

BISPHENOL F - EPOXY RESIN

CAS number	% by weight	EC number	Classification
028064-14-4	20 - 30%		Xi; R36/38, R43, N; R51/53

ALKYL (C13-C15) GLYCIDYL ETHER

CAS number	% by weight	EC number	Classification
068081-84-5	1 - 5%	268-358-2	Xi; R36/38, R43, N; R51/53

See section 16 for the full text of the R-phrases declared above

Occupational exposure limits, if available, are listed in section 8.

### 3. HAZARDS IDENTIFICATION

The preparation is classified as dangerous according to Directive 1999/45/EC and its amendments.

Classification Xi; R36/38, R43, N; R51/53

Human health hazards Irritating to eyes and skin. May cause sensitisation by skin contact.

Environmental hazards Toxic to aquatic organisms. May cause long-term adverse effects in the aquatic environment.

See section 11 for more detailed information on health effects and symptoms.

### 4. FIRST AID MEASURES

Ingestion Do not induce vomiting unless directed to do so by medical personnel.

Never give anything by mouth to an unconscious person. If potentially dangerous

continued on page 2

continued from page 1

quantities of this material have been swallowed, call a physician immediately.

**Skin contact** Wash contaminated skin with soap and water. Remove contaminated clothing and shoes. Wash clothing before reuse. Get medical attention if irritation occurs.

**Eye contact** In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately.

See section 11 for more detailed information on health effects and symptoms.

## **5. FIRE-FIGHTING MEASURES**

**Extinguishing media** In case of fire, use water spray (fog), foam, dry chemical or CO<sub>2</sub>. Do not use water jet.

**Special exposure hazards** No specific hazard.

**Hazardous thermal decomposition products** In a fire, the following may be released: carbon oxides (CO, CO<sub>2</sub>)

**Protection of fire-fighters.** Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## **6. ACCIDENTAL RELEASE MEASURES**

**Personal precautions** Immediately contact emergency personnel. Use suitable protective equipment (section 8).

**Environmental precautions** Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

**Methods for cleaning up** If emergency personnel are unavailable, contain spilt material. For small spills, add absorbent (soil may be used in the absence of other suitable materials), scoop up material and place in a sealable, liquid-proof container for disposal. For large spills, dyke spilt material or otherwise contain it to ensure runoff does not reach a waterway. Place spilt material in an appropriate container for disposal.

## **7. HANDLING AND STORAGE**

**Handling.** Avoid contact with eyes, skin and clothing. Wash thoroughly after handling.

**Storage** Keep container tightly closed. Store in original sealed containers at temperatures between 5° and 30°C.

## **8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Exposure controls**

**Respiratory protection** A respirator is not needed under normal and intended conditions of product use.

**Hand protection** Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. 4-8 hours (breakthrough time): butyl rubber, nitrile rubber, natural rubber (latex) or PVC gloves.

**Eye protection** Safety glasses. Chemical splash goggles. Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts.

continued on page 3

continued from page 2

Skin protection Protective clothing. Repeated or prolonged contact with irritants may cause dermatitis.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Liquid. (Viscous liquid. Colour)	Odour	Faint odour.
pH	Acidic	Boiling point	>200°C (392°F)
Flash point	Closed cup: >240°C (464°F).	Non-flammable.	Flammability
Explosion limits	Not available.	Oxidising properties	Not available
Solubility	Insoluble in cold water.	Vapour density	Not available.
Evaporation rate	Not available.	Octanol/water	Not available.
(butyl acetate = 1)		partition coefficient	
Auto-ignition temperature	>300°C (572°F)	Melting point	Not available.

## 10. STABILITY AND REACTIVITY

### Stability

The product is stable.

### Conditions to avoid

None identified.

### Materials to avoid

This product should be stored away from oxidising materials and strong bases. acids

Amines peroxides These could cause the product to polymerise exothermically.

Unintentional contact with them should be avoided.

### Hazardous decomposition Products

In a fire, the following may be released: carbon oxides (CO, CO<sub>2</sub>)

## 11. TOXICOLOGICAL INFORMATION

### Potential chronic health effects

Inhalation No known significant effects or critical hazards.

Ingestion No known significant effects or critical hazards.

Skin contact Irritating to skin. May cause sensitisation by skin contact.

Eye contact Irritating to eyes.

### Acute toxicity

BISPHENOL A - EPOXY RESIN (Mn ≤700)

Test	Result	Route	Species
LD50	>2000 mg/kg	Oral	Rat

BISPHENOL F - EPOXY RESIN

Test	Result	Route	Species
LD50	>2000 mg/kg	Oral	Rat

### Potential acute health effects

Carcinogenicity No carcinogenic effect.

Mutagenicity No mutagenic effect.

Reproductive toxicity No known significant effects or critical hazards.

### Over-exposure signs/symptoms

Inhalation No known significant effects or critical hazards.

Ingestion No known significant effects or critical hazards

Skin Repeated skin exposure can produce local skin destruction or dermatitis.

### Additional information

No components of this material are listed as carcinogens by OSHA, NTP, ACGIH or IARC.

## 12. ECOLOGICAL INFORMATION

### Persistence/degradability

Ingredient name	Aquatic half-life	Photolysis	Biodegradability
AWF FloorTect H.B. Base	-	-	Not readily

Bioaccumulative potential This product is not expected to bioaccumulate through food chains in the environment.

Mobility Do not allow to enter drains or watercourses.

Other adverse effects Toxic to aquatic organisms. May cause long-term adverse effects in the aquatic environment.

## 13. DISPOSAL CONSIDERATIONS

### Methods of disposal

The generation of waste should be avoided or minimised wherever possible. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

### Hazardous waste

The classification of the product may meet the criteria for a hazardous waste.

## 14. TRANSPORT INFORMATION

International transport regulations

UN number 3082

Proper shipping name Environmentally hazardous substance, liquid, n.o.s.  
(BISPHENOL A - EPOXY RESIN)

Class 9

Packing group III

Additional information Emergency schedules (EmS) F-A,S-F

## 15. REGULATORY INFORMATION

### EU regulations

Hazard symbol/symbols Irritant, Dangerous for the environment.

Risk phrases R36/38- Irritating to eyes and skin. R43- May cause sensitisation by skin contact. R51/53- Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Safety phrases S24- Avoid contact with skin. S24- Avoid contact with skin. S28- After contact with skin, wash immediately with plenty of soap and water. S29- Do not empty into drains. S36/37- Wear suitable protective clothing and gloves. S46- If swallowed, seek medical advice immediately and show this container or label. Contains epoxy constituents. See information supplied by the manufacturer.

### Contains

BISPHENOL A - EPOXY RESIN (Mn <=700) 500-033-5

BISPHENOL F - EPOXY RESIN

ALKYL (C13-C15) GLYCIDYL ETHER 268-358-2

Product use Classification and labelling have been performed according to EU Directives 67/548/EEC and 1999/45/EC (including amendments) and the intended use.

- Consumer applications.

continued on page 5

continued from page 4

Other EU regulations

EU statistical classification                      39073000

(Tariff Code)

National regulations

United States

SARA 313 toxic chemical notification and release reporting    No products were found.

Germany    Hazard class for water 2

<b>16. OTHER INFORMATION</b>
------------------------------

Full text of R-phrases referred to in sections 2 and 3 -Europe

R36/38- Irritating to eyes and skin.R43- May cause sensitisation by skin contact.R51/53- Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Full text of classifications referred to in sections 2 and 3 - Europe

Xn - Harmful

Xi - Irritant

N - Dangerous for the environment.

Further information

Conforms to EU Directive 91/155/EEC, as amended by 2001/58/EC

Canada - This product has been classified according to the hazard criteria of the CPR and the MSDS contains all the information required by the CPR.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Date of issue 05/01/2007